

K5

FLIP FLOW optional


IMPERIAL



The contractors choice due to heavy duty performance, compact transport and high productivity.

Its long screen deck is perfect for precision screening from scalping to fine screening.

The K5 has a large range of screening media available incl. the Bivitec flip flow screen box for very difficult to process materials. Perfect service access and a walkway on the left side of the screen box, which is liftable and can be set in several inclinations.



3,43 US Gal/h
2,37 US Gal/h
1,05 US Gal/h
36 kWh

Applications

- Pre-screening/scalping
- Screening behind or before a crusher
- Top soil
- Separation of "sticky" aggregate
- Construction and demolition waste
- Sand and gravel
- Quarrying and mining
- Coal
- Wood
- Recycling landfill
- And others

Increased uptime and longer service intervals due to Long Life Grease

Maintenance free Return drum bearings (greased for life)

Automatic transport locking system on side conveyors

- Hydraulic folding hopper of HB 450 steel
- Superiour level of surface treatment
- Accessible doors and panels on all sides of the machines for easy maintenance and repair
- Standard equipped with heavy duty apron feeder

Technical specifications	
Capacity up to	500 sT
Weight	31 sT
Screen box (l x w)	17' x 5' & 17' x 4,5'
Feed hopper in HB450	9,1 yard ³
Hydraulic folding hopper for transport	•
Heavy Duty Plate Apron Feeder	10'4" x 3'8"
Loading height	
open back wall	8'8"
half open back wall	9'11"
closed back wall	11'2"
Side loading length	13'9"
Screen box (l x w) standard & bivitec flip flow	17' x 5' & 17' x 4,5'
Upper deck m ²	80,7 ft ² & 72,7 ft ²
Middle deck m ²	/
Lower deck m ²	80,7 ft ² & 72,7 ft ²
Hydraulic liftable screenbox	•
Screen box can be set in several inclinations	6
Standard walkway beside screenbox	Left side
Standard Long Life Grease: grease interval every 250 h	•
Conveyor belts (l x w) & discharge height	
Oversize belt conveyor (discharge height)	16'5" x 3'11" (10'2")
Fine fraction belt conveyor (left) (discharge height)	27'5" x 2'11" (14'4")
Middle fraction belt conveyor (right) (discharge height)	27'2" x 2'8" (12'5")
Track-unit: Length, total width, track shoe width	10'10", 8'2", 1'2"
2-speed track drive	0,8/1,4 mph
Engine unit(s) 1500/1800 RPM	55 kW/55kW, 64 kW/73 kW, 66 kW/78 kW
Control	PLC – IP 67 LCD screen 4,3" & remote control
Smart sequential auto start/stop from remote control	•
Available drive systems	
Diesel/hydraulic drive	•
e-drive Diesel/hybrid, electric plug-in & plug-out	•
ZERO drive (no combustion engine, plug-in electric)	•

OPTIONS

Feeding & screening	
Wear lining in hopper HB 450: 8 mm	•
Severall hopper & corner extensions	•
XXL Hopper	/
Apron feeder (XXL)	/
Feed hopper with belt feeder	•
Inline belt feeder without hopper	/
Overband magnet for Inline belt feeder without hopper	/
Screen flow break	•
Anti clogging system	•
Fast tensioning system for upper deck screens	•
Canvas cover for screen box	•
Walkway beside screenbox	•
Wide range op screen media	•
Bivitex flip flow screen box	•
Volumetric belt scale on apron feeder	•
Conveyors	
Dust suppression system at conveyors	•
Picking station at oversize belt conveyor	Left & right side
Extra long oversize belt conveyor (discharge heigth)	5'10" longer
Over belt magnet on overbelt	•
Over belt magnet on side conveyors	/
Drum magnet and chute on side conveyors	•
Tungsten scrapers	Fines conveyor (left) Under Screen Conveyor
Other options	
Radio remote	•
Working lights	•
Fuel filling pump	•
Heating system for engine unit: diesel and hydraulic tank	•
Keestrack-er Telematics system UMTS/GPS	•
Lifting eyes	•

TRANSPORT	
Transport l x w x h	37'1" x 8'4" x 10'11"

LEGENDA	
•	applicable - available
/	not applicable- not available



IMPERIAL