

R5

IMPERIAL



Liftable magnetic separator

Reliable and compact, transportable with double deck after screen in one piece, easy to set-up without any support legs and highly productive in recycling, aggregates production, quarrying and mining. **The R5e with plug in and plug out functionality, drop off engine/gen set and double deck after screen.**



10,5



Diesel-hydraulic

9,2



Diesel-electric

180



Electric plug-in

mains

Applications

Limestone and many other natural rock
Concrete and landfill recycling
Primary and secondary crushing
Yard clean up
Construction & Demolition waste
Quarrying and mining
Gravel
Asphalt
Coal
And others

Double deck after screen

All drive drums and return drums of belt conveyors are greased for life

- Independent 2-deck pre screen for better crushing capacities and less wear
- Rotor design with high mass of inertia and blow bars designed for a longer lifetime
- Patented tilting chassis
- Transport with Dolly system possible
- Under screen conveyor to prevent material build up under the pre screen

Keestrack

TECHNICAL SPECIFICATIONS	
Capacity up to	440 sT
Weight	50 sT
Weight incl. single deck after screen	/
Weight incl. double deck after screen	55 sT
Inlet opening	31" x 41"
Hopper	6,5 yard ³
Feed hopper in HB450 and wear lining in HB 450 & 500	•
Hydraulic foldable hopper walls	• (left & right)
Loading height	11'1" rear, 12'1" sides
	Loading width (back) 9'6"
	Side loading length 12'6" right, 9'11" left
	Wear lining HB 450 welded/ HB 500 return conveyor discharge & bottom
Vibrating feeder with pre-screen, l x w	n/a
Pre-screen scalper, l x w	n/a
Screened fraction either in crusher bypass or separately stockpiled (option)	n/a
Vibrating feeder, l x w	7'3" x 3'3"
Independent vibrating Double Deck pre-screen	•
Double deck pre-screen, l x w top deck	7'3" x 3'3"
Double deck pre-screen, l x w bottom deck	5'11" x 3'3"
Under screen conveyor: Reversible, to crusher bypass or to side conveyor	5'9" x 2'8"
Fine fraction either in crusher bypass or separately stockpiled (option)	•
Intermediate fraction in crusher bypass	•
Intermediate fraction either in crusher bypass or separately stockpiled (option)	•
Turnable heavy duty bar for edge protection in inlet	•
Impact Crusher	
Weight of impact crusher (excl. milling beam)	13 sT
Inlet opening	2'8" x 3'5"
Rotor width	3'3"
Rotor diameter	4'2"
Rotor weight (excl. Bearings)	5,6 sT
Impact aprons	2 pcs
Hydraulic release system inlet area via remote control	•
Hydraulic setting of aprons, turning spindle for fixation of the back stop.	•
Spring force adjustments and shiming plates fixation"	
Standard access to crusher house	left side
Vibrating discharge feeder (l x w)	10'5" x 3'4"
Main conveyor belt (l x w) & (discharge height)	30'5" x 3'11" (14'5")
Main conveyor belt height adjustable at discharge and lowerable mechanism	•
Main conveyor hydraulic foldable for transport	/
Track-unit: Length, total width, track shoe width	13'7", 8'10", 1'6"
2-speed track drive	0,7 and 1,2 mph
Drop-off engine	•
Engine unit(s), indication, sometimes more optional engines	352 kW @ 1500 RPM, 382 kW @ 1800 RPM
Control	PLC – IP 67 LCD screen 7" & remote control
Smart sequential auto start/stop from remote control	•
Safety protection with special key system, emergency stops, machine stop at remote, protected doors during operation and other safety features	•
All drive drums and return drums of belt conveyors are greased for life	•
Patented tilting chassis for increased maintenance access and to increase feed capacity if needed	•
Available drive systems	
	Diesel/hydraulic drive •
	Rotor direct driven by engine, electric driven components /
	e-drive Diesel/hybrid, electric plug-in & plug-out •
	ZERO drive (no combustion engine, plug-in electric) •

OPTIONS

Feeding , pre-screen & crushing	
Hopper extensions	12 yard ³
Screen media pre-screen	Range of punched plates, screen plates and Zig zag-shaped or blind plate, wire mesh bottom deck
Stockpiling Side belt conveyor from pre-screen l x w (discharge height)	14'3" x 2'2" (9'6")
Milling beam	/
Deviation plates	•
Several quality blow bars	•
Swiveling arm and hoist to change blow bars	•
Frequency inverter for crusher drive on e-version	•
After screen	
Single deck after screen: l x w, incl oversize, recycling and fines conveyor	n/a
Oversize stockpile conveyor l x w (discharge height)	n/a
2- deck after screen: incl oversize, recycling and fines conveyor for closed circuit processing.	•
After screen unit can be disassembled easy by fast connectors and can be placed on support legs	
Top deck, l x w	15'7" x 5'
Bottom deck, l x w	15'1" x 5'
Screen media after screen	Wire mesh / square mesh / Harp screen
Middle fraction stockpile conveyor, l x w (discharge height)	21' x 2'2" (10'9")
Fines conveyor, l x w (discharge height)	22'4" x 3'11" (13'5")
Swiveling recycling conveyor can be used as recycling conveyor (closed circuit) / stockpile conveyor oversize fraction (hydraulic foldable)	•
Walkways besides the screen box	left & right
Other options	
Wheeled dolly	•
Dust suppression system at crusher inlet and outlet or at end of main and fines conveyor	•
Height adjustable magnet separator on main conveyor	•
Wind sifter (air knife) for oversize fraction	•
Dust cover main conveyor / fines conveyor	•
Volumetric belt scale	•
Radio remote, several options	•
Fuel filling pump	•
Central greasing system	•
Working lights	•
Telematics system UMTS/GPS	•
Heating system for engine	•
Lifting eyes	•

TRANSPORT	
Transport l x w x h	53'9" x 9'11" x 11'10"
Transport l x w x h 1-deck	/
Transport l x w x h 2-deck	56'5" x 9'11" x 11'10"

LEGENDA	
•	applicable - available
/	not applicable- not available

