

# MOBILE DOUBLEScreens PIONEERING SOLUTIONS FOR YOU



Leading the way in mobile screening technology, our Doublescreen technology is the stand-out feature of any mobile screen in the market today.

Our Doublescreen is a revolutionary design utilizing two high velocity screen boxes to achieve a higher throughput and increased screening efficiency. Unique to Sandvik, this technology utilizes two inline, independent screenboxes which can be independently angled, offering a marked increase in throughput, control and screening efficiency compared to a traditional single box.

Offering an unsurpassed level of separation on a wide range of materials, at very high production rates, the Doublescreen system is available in a double deck or triple deck form and offers you a screening solution that no other mobile screener can provide.

## KEY BENEFITS

- Massive production capabilities due to the substantial screening area
- Independently adjustable screenbox angles delivering ultimate precision screening \*\*
- Large volume hopper complete with remote control hydraulic tipping grid
- User friendly control panel with sequential start-up for ease of operation
- Full radio remote control as standard for safe and easy manoeuvrability
- Hybrid drive option with electric plug in available to run in diesel-hydraulic or diesel-electric mode\*
- Fitted with My Fleet telematics with 7 year data subscription as standard



KEY SPECIFICATIONS	QA452 Doublescreen **	QA441 Doublescreen **	QA335 Doublescreen
Screen box	20' x 5' / 6.00 m x 1.50 m Triple deck	20' x 5' / 6.00 m x 1.50 m Double deck	13' x 5' / 3.96 m x 1.52 m Double deck
Engine	CAT C4.4 Stage 5 / T4F 98 kW / 132 hp Stage 3A LRC*** 96 kW / 129 hp CAT NR4 (China) 110 kW / 147 hp JCB Stage 5 97 kW 130 hp JCB T4F 93 kW / 125 hp JCB 3A ROW 97 kW / 130 hp	CAT C4.4 Stage 5 / T4F 98 kW / 132 hp CAT C4.4 Stage 3A Constant Speed 98 kW / 132 hp CAT NR4 (China) 110 kW / 147 hp	CAT C2.8 Stage 5 / T4F 55 kW / 74 hp CAT C2.8 Stage 3A LRC *** 55 kW / 74 hp CAT NR4 (China) 110 kW / 147 hp
Transport dimensions	18.37 m / 60' 3" (l) 3.20 m / 10' 6" (w) 3.60 m / 11' 10" (h)	18.49 m / 60' 7" (l) 3.20 m / 10' 5" (w) 3.55 m / 11' 6" (h)	15.35 m / 50' 3" (l) 3.00 m / 9' 10" (w) 3.40 m / 11' 2" (h)
Weight	36,200 kg / 79,810 lbs	31,762 kg / 70,023 lbs	26,520 kg / 58,467 lbs

\*Available on QA452 and QA441

\*\* Not all models

\*\*\* Lesser Regulated Countries