

USED EQUIPMENT

Keestrack R3 Impact Crusher

also r3e,r3e0, r3h versions

- Available in full hybrid e version
- Equipped in closed circuit < 30.000 kg, easy to transport without permit
- Hopper 3,5 m³ (4,5 yard³)
- Vibrating feeder with punched plate pre screen 1.200 mm x 920 mm (4' x 3')



- Due to integrated pre screen, higher crushing capacities and less wear
 - Inlet opening (H x W) 770 x 960 mm (30" x 38")
 - Superior rotor diameter 1.100 mm (44")
 - Optional 3rd impact panel as milling beam to produce high value end product
 - Optional single deck after screen 3.100 x 1.400 mm (9' x 4')
 - Capacity up to 250 tonnes / hour
 - Load sensing hydraulic system reduces fuel usage by 25%
 - 2 speed track drive
 - Highest reduction ratio
 - Superior product shape
 - Extensive option list to configure to your application
- Optional windsifter

	Transport dimensions	Transport dimensions with after screen		Working length without after screen	Working length with after screen
Weight	27,5t (30sT)	± 33,2 t (36 sT)			
Length	10.000 mm (32'10")	12.900 mm (42'4")	1	1.525 mm (37'10")	14.218 mm (46'8")
Height	3.200 mm (10'6")	3.200 mm (10'6")			
Width	2.540 mm (8'4")	2.540 mm (8'4")			
Width	2.720 mm (8'10")	14.400 mm (47'3")			
Width	2.550 mm (8'4")	14.010 mm (46')			
Width	2.725 mm (8'10")	6.045 mm (20')			